



# 3 **NEW** PRE-DOSED EPOXART KITS

A simple and convenient professional solution for reinforcing, resining, and repairing.



## EPOXART KIT 2TO1 - 50% (2:1)

EPOXART A-5008 Kg 1 • EPOXART B-BM50 Kg 0.5

Epoxy system to **resin, and reinforce with fiberglass** stone materials. The use of this epoxy system is particularly suitable where **high penetration** is required, in case of **micro-cracks** or when you want to **increase the tone of the material**.

- + **LOW VISCOSITY**
- + **MEDIUM HARDNESS**
- + **SUPERB ADHESION**
- + **COLOUR INCREASE**

Gel time (mass at 77°): 55-75 min  
Workability time (77°): 24 hours

Part # EPOXARTKIT2TO1

## EPOXART KIT 3TO1 - 30% (3:1)

EPOXART A-5004 Kg 1 • EPOXART B-BM30 Kg 0.3

Epoxy system to **resin and reinforce with fiberglass** stone materials. The use of this epoxy system is particularly suitable where **high transparency** in the cracks of the material, **high penetration**, and **slow hardening** time are required or for the **creation of small masses of resin**.

- + **LOW VISCOSITY**
- + **MEDIUM HARDNESS**
- + **GOOD REACTIVITY TO COLD**
- + **EXCELLENT STABILITY TO SUNLIGHT**

Gel time (mass at 77°): 150-180 min  
Workability time (77°): 24-48 hours

Part # EPOXARTKIT3TO1

## EPOXART KIT 4TO1 - 25% (4:1)

EPOXART A-1006 Kg 1 • EPOXART B-BB25 Kg 0.25

**Fast** epoxy system to **resin and reinforce with fiberglass** stone materials. the use of this epoxy system is particularly suitable where a **natural effect** is required, without altering the colour of the material. Its formulation combines **the high reaction speed** with **low yellowing over time**.

- + **MEDIUM VISCOSITY**
- + **MEDIUM HARDNESS**
- + **SUPERB REACTIVITY TO COLD**
- + **GOOD STABILITY TO SUNLIGHT**

Gel time (mass at 77°): 7-8 min  
Workability time (77°): 6-8 hours

Part # EPOXARTKIT4TO1

**FOR MORE INFORMATION: Email: [sales@tenaxusa.com](mailto:sales@tenaxusa.com) or phone: 704-583-1173**