

BLACK67

Revision nr.2 Dated 10/15/2019 Printed on 10/15/2019 Page n. 1/10 Replaced revision:1 (Dated 6/28/2019)

Safety Data Sheet

According to Canadian HPR - WHMIS 2015

1. Identification

1.1. Product identifier

Product name **BLACK67**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified Uses	Industrial	Professional	Consumer			
ADHESIVE SYSTEM/TREATMENT FOR STONE						
SECTOR	-	\checkmark	-			
3. Details of the supplier of the safety data sheet						
Name	Tenax Spa					
Full address	Via I Maggio, 226					
District and Country	37020 Volargne	(1	VR)			
	Italy Tel. +39 045 6887593					
	Tel. +39 045 6887593 Fax +39 045 6862456					
e-mail address of the competent person	FAX +39 043 0002430					
responsible for the Safety Data Sheet	msds@tenax.it					
	J					
Product distribution by:	Tenax Usa					
	7606 Whitehall Executive	•	28273 Charlotte NC, US			
	Tel. 001 7045831173 - Fax	x 001 7045833166				
	info@tenaxusa.com					
4. Emergency telephone number						
For urgent inquiries refer to	24hrs:					
	Manitoba Poison Centre	1-855-7POISON (1-855-77	76-4766)			
	BC Drug and Poison Info	ormation Centre (DPIC)				
	1-800-567-8911 (toll free					
	(604) 682-5050 (Greater V	•	3C)			
	Centre antipoison du Qu	ébec 1-800-463-5060				
	IWK Regional Poison Ce	ntre				
	1-800-565-8161 (within N					
	(902) 470-8161 (Halifax o					
	Poison And Drug Informa	ation Services (DADIS)				
	FUISON AND DING MIDING	ation Jei vices (FADIS)				
	1-800-332-1414 (tall free	in Alberta Northwest Tor	ritories)			
	1-800-332-1414 (toll free 1-866-454-1212 (toll free		ritories)			

2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in Canada's Hazardous Products Regulations (HPR) (WHMIS 2015). The product thus requires a safety datasheet.

Ontario Poison Centre 1-800-268-9017

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Classification and Hazard Statement Flammable liquid, category 4 Acute toxicity, category 4

Combustible liquid. Harmful if swallowed.



BLACK67

Revision nr.2 Dated 10/15/2019 Printed on 10/15/2019 Page n. 2 / 10 Replaced revision:1 (Dated 6/28/2019)

2. Hazards identification

Acute toxicity, category 4 Eye irritation, category 2 Skin irritation, category 2 Harmful if inhaled. Causes serious eye irritation. Causes skin irritation.

Hazard pictograms:



Warning Signal words:

Hazard statements:

H227 Combustible liquid.

H302+H332 Harmful if swallowed or if inhaled. H319 Causes serious eye irritation. Causes skin irritation. H315

Precautionary statements:

Prevention:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P210

P261 Avoid breathing dust / fume / gas / mist / vapours / spray. P280 Wear protective gloves / eye protection / face protection. P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area. P264 Wash the hands thoroughly after handling.

Response:

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Call a POISON CENTRE / doctor / . . . if you feel unwell. P312 P332+P313 If skin irritation occurs: Get medical advice / attention. If eye irritation persists: Get medical advice / attention. P337+P313

IF INHALED: remove person to fresh air and keep comfortable for breathing. P304+P340

P330 Rinse mouth.

P362+P364 Take off contaminated clothing and wash it before reuse. P370+P378 In case of fire: use CO2, sand, powder to extinguish.

Storage:

P403+P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents / container according to applicable law.

The mixture contains 32.00% of components of unknown acute inhalation toxicity.

2.2. Other hazards

Information not available

Composition/information on ingredients

3.2. Mixtures

Contains:

Identification Classification: x = Conc. % (w/w)

2-BUTOXYETHANOL

ETHYLENE GLYCOL MONOBUTYL ETHER

BUTYL CELLOSOLVE

CAS 111-76-2 40 Flammable liquid, category 4 H227, Acute toxicity, category 4 H302, Acute toxicity, category 4 H312, Acute toxicity, category 4 H332, Eye irritation, category 2 H319,

Skin irritation, category 2 H315



Revision nr.2 Dated 10/15/2019 Printed on 10/15/2019 Page n. 3 / 10

Page n. 3 / 10 Replaced revision:1 (Dated 6/28/2019)

3. Composition/information on ingredients/

2-(2-BUTOXYETHOXY)ETHANOL

BUTYLDIGLYCOL

DIETHYLENE GLYCOL MONOBUTYL ETHER

CAS 112-34-5 32

Eye irritation, category 2 H319

The full wording of hazard (H) phrases is given in section 16 of the sheet.

4. First-aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

5. Fire-fighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.



Revision nr.2 Dated 10/15/2019 Printed on 10/15/2019 Page n. 4 / 10 Replaced revision:1 (Dated 6/28/2019)

6. Accidental release measures .../>>

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition.

7.3. Specific end use(s)

Information not available

8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

EU OEL EU Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC;

Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.

TLV-ACGIH ACGIH 2019

				2-BUTO)	KYETHANC)L	
Threshold Limit	Value						
Type	Country	TWA/8h		STEL/15i	min		
		mg/m3	ppm	mg/m3	ppm		
OEL	EU	98	20	246	50	SKIN	
TLV-ACGIH	-	97	20				
OSHA	USA	240	50			SKIN	

2-(2-BUTOXYETHOXY)ETHANOL						
Threshold Limit Value						
Type	Country	TWA/8h	STEL/15min		5min	
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH	-	66	10			
OEL	EU	67.5	10	101.2	15	

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

TLV of solvent mixture: 97 mg/m3

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must comply with current regulations.

HAND PROTECTION

Protect hands with category III work gloves (OSHA 29 CFR 1910.138).



BLACK67

Revision nr.2 Dated 10/15/2019 Printed on 10/15/2019 Page n. 5 / 10 Replaced revision:1 (Dated 6/28/2019)

Exposure controls/personal protection

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability. The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear. Wash body with soap and water after removing protective clothing. **EYE PROTECTION**

Wear airtight protective goggles (OSHA 29 CFR 1910.133, CSA Standard CAN/CSA-Z94.3-92).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134, CSA Standard Z94.4-02). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84, OSHA 29 CFR 1910.134, CSA Standard Z94.4-02.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	Not available	
Colour	Not available	
Odour	Not available	
Odour threshold	Not available	
pH	Not available	
Melting point / freezing point	Not available	
Initial boiling point	Not available	
Boiling range	Not available	
Flash point	60 < T ≤ 93 °C	(140 < T ≤ 199,4 °F)
Evaporation Rate	Not available	,
Flammability of solids and gases	Not available	
Lower inflammability limit	Not available	
Upper inflammability limit	Not available	
Lower explosive limit	Not available	
Upper explosive limit	Not available	
Vapour pressure	Not available	
Vapour density	Not available	
Relative density	0.98	
Solubility	Not available	
Partition coefficient: n-octanol/water	Not available	
Auto-ignition temperature	Not available	
Decomposition temperature	Not available	
Viscosity	Not available	
Explosive properties	Not available	
Oxidising properties	Not available	

9.2. Other information

Information not available

10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

2-BUTOXYETHANOL

Decomposes under the effect of heat.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.



Revision nr.2 Dated 10/15/2019 Printed on 10/15/2019 Page n. 6 / 10

Page n. 6 / 10 Replaced revision:1 (Dated 6/28/2019)

10. Stability and reactivity

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

2-BUTOXYETHANOL

May react dangerously with: aluminium,oxidising agents. Forms peroxides with: air.

2-(2-BUTOXYETHOXY)ETHANOL

May react with: oxidising substances. May form peroxides with: oxygen. Develops hydrogen on contact with: aluminium. May form explosive mixtures with: air.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

2-BUTOXYETHANOL

Avoid exposure to: sources of heat,naked flames.

2-(2-BUTOXYETHOXY)ETHANOL

Avoid exposure to: air.

10.5. Incompatible materials

2-(2-BUTOXYETHOXY)ETHANOL

Incompatible with: oxidising substances, strong acids, alkaline metals.

10.6. Hazardous decomposition products

2-BUTOXYETHANOL

May develop: hydrogen. 2-(2-BUTOXYETHOXY)ETHANOL May develop: hydrogen.

11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

2-(2-BUTOXYETHOXY)ETHANOL

 LD50 (Oral)
 3384 mg/kg Rat

 LD50 (Dermal)
 2700 mg/kg Rabbit

2-BUTOXYETHANOL

 LD50 (Oral)
 615 mg/kg Rat

 LD50 (Dermal)
 405 mg/kg Rabbit

 LC50 (Inhalation)
 2.2 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION



Revision nr.2 Dated 10/15/2019 Printed on 10/15/2019
Page n. 7 / 10
Replaced revision:1 (Dated 6/28/2019)

Toxicological information

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

Carcinogenicity Assessment:

111-76-2 2-BUTOXYETHANOL

> ACGIH:: A3 IARC:3

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

2-BUTOXYETHANOL

LC50 - for Fish 1474 mg/l/96h Oncorhynchus mykiss

1550 mg/l/48h Daphnia magna EC50 - for Crustacea

EC50 - for Algae / Aquatic Plants 1840 mg/l/72h Pseudokirchneriella subcapitata

Chronic NOEC for Fish > 100 mg/l Brachydanio rerio - NOEC 21d

Chronic NOEC for Crustacea 100 mg/l Daphnia magna - NOEC 21d

12.2. Persistence and degradability

2-(2-BUTOXYETHOXY)ETHANOL

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

2-BUTOXYETHANOL

1000 - 10000 mg/l Solubility in water

Rapidly degradable

@EPY 9.11.0 - SDS 1004.13



Revision nr.2 Dated 10/15/2019 Printed on 10/15/2019 Page n. 8 / 10 Replaced revision:1 (Dated 6/28/2019)

Ecological information

12.3. Bioaccumulative potential

2-(2-BUTOXYETHOXY)ETHANOL

Partition coefficient: n-octanol/water 1

2-BUTOXYETHANOL

0.81 Partition coefficient: n-octanol/water

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Substances subject to the Rotterdam Convention:



BLACK67

Revision nr.2 Dated 10/15/2019 Printed on 10/15/2019 Page n. 9 / 10

Page n. 9 / 10 Replaced revision:1 (Dated 6/28/2019)

15. Regulatory information .../>>

None

Canadian Regulatory Information

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR).

Safety Data Sheet according to WHMIS 2015.

16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

H227 Combustible liquid. H302 Harmful if swallowed.

H302+H332 Harmful if swallowed or if inhaled.
H312 Harmful in contact with skin.

H332 Harmful if inhaled.
H319 Causes serious eye irritation.
H315 Causes skin irritation.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CLP: EC Regulation 1272/2008
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

GENERAL BIBLIOGRAPHY:

- GHS rev. 5
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh Registry of Toxic Effects of Chemical Substances
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy
- Hazard Products Regulation (HPR)
- WHMIS 2015
- ONTARIO R.R.O. 1990, Regulation 883 (version July 2016)
- IARC website
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current



Revision nr.2 Dated 10/15/2019 Printed on 10/15/2019 Page n. 10 / 10 Replaced revision:1 (Dated 6/28/2019)

16. Other information .../>>

health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the criteria set out in Canada's Hazardous Products Regulations (HPR) (WHMIS 2015), unless otherwise indicated in sections 11 and 12.

The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review: The following sections were modified: 02 / 03 / 12.