

Safety Data Sheet

According to U.S.A. Federal Hazcom 2012

1. Identification

1.1. Product identifier

Product name **DAKOS 280 W 2**
Chemical name and synonym **RESINA POLIESTERE IN STIRENE FOTOSENSIBILE**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Light-sensitive polyester resin for stones filling.**

Identified Uses	Industrial	Professional	Consumer
ADHESIVE SYSTEM/TREATMENT FOR STONE SECTOR	-	✓	-

1.3. Details of the supplier of the safety data sheet

Name **Tenax Spa**
Full address **Via I Maggio, 226**
District and Country **37020 Volargne Italy (VR)**
Tel. **+39 045 6887593**
Fax **+39 045 6862456**

e-mail address of the competent person responsible for the Safety Data Sheet **msds@tenax.it**

Product distribution by: **Tenax Usa**
7606 Whitehall Executive Center Drive Suite 400, 28273 Charlotte NC, US
Tel. 001 7045831173 - Fax 001 7045833166
info@tenaxusa.com

1.4. Emergency telephone number

For urgent inquiries refer to **Infotrac**
US and Canada: 1-800-535-5053
Int'l: 1-352-323-3500
info@infotrac.net

2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200). The product thus requires a safety datasheet.
Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Classification and Hazard Statement

Flammable liquid, category 3	Flammable liquid and vapour.
Reproductive toxicity, category 2	Suspected of damaging fertility or the unborn child.
Specific target organ toxicity - repeated exposure, category 1	Causes damage to organs through prolonged or repeated exposure.
Eye irritation, category 2	Causes serious eye irritation.
Skin irritation, category 2	Causes skin irritation.
Skin sensitization, category 1	May cause an allergic skin reaction.

Hazard pictograms:



Tenax Spa

DAKOS 280 W 2

Revision nr.1
Dated 12/17/2018
First compilation
Printed on 11/11/2020
Page n. 2 / 11

2. Hazards identification ... / >>

Signal words: Danger

Hazard statements:

H226 Flammable liquid and vapour.
H361 Suspected of damaging fertility or the unborn child.
H372 Causes damage to organs through prolonged or repeated exposure.
H319 Causes serious eye irritation.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.

Precautionary statements:

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe dust / fume / gas / mist / vapours / spray.
P202 Do not handle until all safety precautions have been read and understood.
P242 Use only non-sparking tools.
P201 Obtain special instructions before use.
P233 Keep container tightly closed.
P280 Wear protective gloves/ protective clothing / eye protection / face protection.
P270 Do not eat, drink or smoke when using this product.
P264 Wash the hands thoroughly after handling.
P240 Ground / bond container and receiving equipment.
P243 Take precautionary measures against static discharge.
P241 Use explosion-proof electrical / ventilating / lighting / . . . / equipment.
P272 Contaminated work clothing should not be allowed out of the workplace.

Response:

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water / shower.
P308+P313 IF exposed or concerned: Get medical advice / attention.
P314 Get medical advice / attention if you feel unwell.
P333+P313 If skin irritation or rash occurs: Get medical advice / attention.
P337+P313 If eye irritation persists: Get medical advice / attention.
P302+P352 IF ON SKIN: wash with plenty of water / . . .
P362+P364 Take off contaminated clothing and wash it before reuse.
P370+P378 In case of fire: use CO₂, sand, powder to extinguish.
P363 Wash contaminated clothing before reuse.

Storage:

P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents / container according to applicable law.

2.2. Other hazards

Information not available

3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	Conc. %	Classification:
STYRENE		
CAS	100-42-5 27.388	Flammable liquid, category 3 H226, Reproductive toxicity, category 2 H361, Acute toxicity, category 4 H332, Specific target organ toxicity - repeated exposure, category 1 H372, Eye irritation, category 2 H319, Skin irritation, category 2 H315
EC	202-851-5	
INDEX	601-026-00-0	
TRIMETHYLOLPROPANE TRIACRYLATE		
CAS	15625-89-5 9.26	Eye irritation, category 2 H319, Skin irritation, category 2 H315, Skin sensitization, category 1 H317
EC	239-701-3	
INDEX	607-111-00-9	

The full wording of hazard (H) phrases is given in section 16 of the sheet.

4. First-aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

5. Fire-fighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

Tenax Spa

DAKOS 280 W 2

Revision nr.1
Dated 12/17/2018
First compilation
Printed on 11/11/2020
Page n. 4 / 11

6. Accidental release measures ... / >>

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

USA	NIOSH-REL	NIOSH publication No. 2005-149, 3th printing, 2007.
USA	OSHA-PEL	Occupational Exposure Limits - Limits for Air Contaminants TABLE Z-1-1910.1000.
USA	CAL/OSHA-PEL	California Division of Occupational Safety and Health (Cal-OSHA) Permissible Exposure Limits (PELs).
	TLV-ACGIH	ACGIH 2019

STYRENE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH	-	85	20	170	40	
OSHA	USA		100		200 (C)	
CAL/OSHA	USA	215	50	425 (C)	500 (C)	SKIN
NIOSH	USA	215	50	425	100	

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

TLV of solvent mixture: 85 mg/m3

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must comply with current regulations.

HAND PROTECTION

Protect hands with category III work gloves (OSHA 29 CFR 1910.138).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear. Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

Tenax Spa

DAKOS 280 W 2

Revision nr.1
Dated 12/17/2018
First compilation
Printed on 11/11/2020
Page n. 5 / 11

8. Exposure controls/personal protection ... / >>

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84, OSHA 29 CFR 1910.134.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	colourless	
Odour	typical	
Odour threshold	Not available	
pH	Not available	
Melting point / freezing point	Not available	
Initial boiling point	Not available	
Boiling range	Not available	
Flash point	32 °C	(89,6 °F)
Evaporation Rate	Not available	
Flammability of solids and gases	Not available	
Lower inflammability limit	Not available	
Upper inflammability limit	Not available	
Lower explosive limit	Not available	
Upper explosive limit	Not available	
Vapour pressure	Not available	
Vapour density	Not available	
Relative density	Not available	
Solubility	insoluble in water	
Partition coefficient: n-octanol/water	Not available	
Auto-ignition temperature	Not available	
Decomposition temperature	Not available	
Viscosity	>10 mm ² /sec (DIN ISO Cup 3 mm)	
Explosive properties	Not available	
Oxidising properties	Not available	

9.2. Other information

Information not available

10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

STYRENE

Polymerises at temperatures above 65°C/149°F. Fire hazard. Possibility of explosion.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

STYRENE

May react dangerously with: peroxides, strong acids. May polymerise on contact with: aluminium trichloride, azobisisobutyronitrile, dibenzoyl peroxide, sodium. Risk of explosion on contact with: butyllithium, chlorosulphuric acid, di-tert-butyl peroxide, oxidising substances, oxygen.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

Tenax Spa

DAKOS 280 W 2

Revision nr.1
Dated 12/17/2018
First compilation
Printed on 11/11/2020
Page n. 6 / 11

10. Stability and reactivity ... / >>

STYRENE

Avoid contact with: oxidising substances, copper, strong acids.

10.5. Incompatible materials

STYRENE

Incompatible materials: plastic materials.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

STYRENE

LD50 (Oral)

5000 mg/kg Rat

LC50 (Inhalation)

11.8 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

Carcinogenicity Assessment:

100-42-5

STYRENE

ACGIH:: A4

IARC:2B

NTP: Reasonably Anticipated

Tenax Spa

DAKOS 280 W 2

Revision nr.1
Dated 12/17/2018
First compilation
Printed on 11/11/2020
Page n. 7 / 11

11. Toxicological information ... / >>

REPRODUCTIVE TOXICITY

Suspected of damaging fertility or the unborn child

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Causes damage to organs

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class Viscosity: >10 mm²/sec (DIN ISO Cup 3 mm)

12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

Information not available

12.2. Persistence and degradability

STYRENE

Solubility in water 320 mg/l
Rapidly degradable

TRIMETHYLOLPROPANE TRIACRYLATE

Solubility in water 100 - 1000 mg/l
Rapidly degradable

12.3. Bioaccumulative potential

STYRENE

Partition coefficient: n-octanol/water 2.96

BCF 74

TRIMETHYLOLPROPANE TRIACRYLATE

Partition coefficient: n-octanol/water 0.67

12.4. Mobility in soil

STYRENE

Partition coefficient: soil/water 2.55

TRIMETHYLOLPROPANE TRIACRYLATE

Partition coefficient: soil/water 2.2

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

Tenax Spa

DAKOS 280 W 2

Revision nr.1
Dated 12/17/2018
First compilation
Printed on 11/11/2020
Page n. 8 / 11

12. Ecological information ... / >>

12.6. Other adverse effects

Information not available

13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

14. Transport information

14.1. UN number

ADR / RID, IMDG, IATA: 1866

14.2. UN proper shipping name

ADR / RID: RESIN SOLUTION
IMDG: RESIN SOLUTION
IATA: RESIN SOLUTION

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3



IMDG: Class: 3 Label: 3



IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards

ADR / RID: NO
IMDG: NO
IATA: NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 30 Special Provision: -	Limited Quantities: 5 L	Tunnel restriction code: (D/E)
IMDG:	EMS: F-E, S-E	Limited Quantities: 5 L	
IATA:	Cargo: Pass.: Special Instructions:	Maximum quantity: 220 L Maximum quantity: 60 L A3	Packaging instructions: 366 Packaging instructions: 355

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

U.S. Federal Regulations

Tenax Spa

DAKOS 280 W 2

Revision nr.1
Dated 12/17/2018
First compilation
Printed on 11/11/2020
Page n. 9 / 11

15. Regulatory information ... / >>

TSCA:

All components are listed on TSCA Inventory.

Clean Air Act Section 112(b):
100-42-5 STYRENE

Clean Air Act Section 602 Class I Substances:
No component(s) listed.

Clean Air Act Section 602 Class II Substances:
No component(s) listed.

Clean Water Act – Priority Pollutants:
No component(s) listed.

Clean Water Act – Toxic Pollutants:
No component(s) listed.

DEA List I Chemicals (Precursor Chemicals):
No component(s) listed.

DEA List II Chemicals (Essential Chemicals):
No component(s) listed.

EPA List of Lists:
313 Category Code:
100-42-5 STYRENE

EPCRA 302 EHS TPQ:
No component(s) listed.

EPCRA 304 EHS RQ:
No component(s) listed.

CERCLA RQ:
100-42-5 STYRENE

EPCRA 313 TRI:
100-42-5 STYRENE

RCRA Code:
No component(s) listed.

CAA 112 (r) RMP TQ:
No component(s) listed.

State Regulations

Massachusetts:
100-42-5 STYRENE

Minnesota:
100-42-5 STYRENE
15625-89-5 TRIMETHYLOLPROPANE TRIACRYLATE

New Jersey:
100-42-5 STYRENE

New York:
100-42-5 STYRENE

Pennsylvania:
100-42-5 STYRENE

California:
100-42-5 STYRENE

Proposition 65:
WARNING! This product contains chemicals known to the State of California to cause cancer and birth defects or reproductive harm.

Tenax Spa

DAKOS 280 W 2

Revision nr.1
Dated 12/17/2018
First compilation
Printed on 11/11/2020
Page n. 10 / 11

15. Regulatory information ... / >>

100-42-5 STYRENE C

International Regulations

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Canadian WHMIS

Information not available

16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

H226	Flammable liquid and vapour.
H361	Suspected of damaging fertility or the unborn child.
H332	Harmful if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.

LEGEND:

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAA 112 @ RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112@)
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: EC Regulation 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

GENERAL BIBLIOGRAPHY:

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh - Registry of Toxic Effects of Chemical Substances
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition

Tenax Spa

DAKOS 280 W 2

Revision nr.1
Dated 12/17/2018
First compilation
Printed on 11/11/2020
Page n. 11 / 11

- ECHA website- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy
- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Communication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112© of the Clean Air Act
- Massachusetts 105 CMR Department of public health 670.000: "Right to Know"
- Minnesota Chapter 5206 Department Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Product classification derives from criteria established by the OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200), unless determined otherwise in Section 11 and 12. The data for evaluation of chemical-physical properties are reported in section 9.