

# Tenax Spa

## DOMOCOMB-B-LIQUID

Revision nr.1  
Dated 10/30/2019  
First compilation  
Printed on 11/6/2020  
Page n. 1 / 12

### Safety Data Sheet

According to U.S.A. Federal Hazcom 2012

#### 1. Identification

##### 1.1. Product identifier

Product name **DOMOCOMB-B-LIQUID**

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **EPOXY MASTIC PART B**

##### 1.3. Details of the supplier of the safety data sheet

Name **Tenax Spa**  
Full address **Via I Maggio, 226**  
District and Country **37020 Volargne (VR)**  
**Italy**  
Tel. **+39 045 6887593**  
Fax **+39 045 6862456**

e-mail address of the competent person responsible for the Safety Data Sheet **msds@tenax.it**

Product distribution by: **Tenax Usa**  
**7606 Whitehall Executive Center Drive Suite 400, 28273 Charlotte NC, US**  
Tel. **001 7045831173** - Fax **001 7045833166**  
**info@tenaxusa.com**

##### 1.4. Emergency telephone number

For urgent inquiries refer to **Infotrac**  
**US and Canada: 1-800-535-5053**  
**Int'l: 1-352-323-3500**  
**info@infotrac.net**

#### 2. Hazards identification

##### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200). The product thus requires a safety datasheet.  
Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

##### Classification and Hazard Statement

Carcinogenicity, category 2	Suspected of causing cancer.
Skin corrosion, category 1	Causes severe skin burns and eye damage.
Serious eye damage, category 1	Causes serious eye damage.
Skin sensitization, category 1	May cause an allergic skin reaction.

##### Hazard pictograms:



Signal words: **Danger**

##### Hazard statements:

<b>H351</b>	Suspected of causing cancer.
<b>H314</b>	Causes severe skin burns and eye damage.
<b>H317</b>	May cause an allergic skin reaction.

##### Precautionary statements:

# Tenax Spa

## DOMOCOMB-B-LIQUID

Revision nr.1  
Dated 10/30/2019  
First compilation  
Printed on 11/6/2020  
Page n. 2 / 12

### 2. Hazards identification ... / >>

#### Prevention:

- P260** Do not breathe dust / fume / gas / mist / vapours / spray.  
**P202** Do not handle until all safety precautions have been read and understood.  
**P201** Obtain special instructions before use.  
**P280** Wear protective gloves/ protective clothing / eye protection / face protection.  
**P264** Wash the hands thoroughly after handling.  
**P272** Contaminated work clothing should not be allowed out of the workplace.

#### Response:

- P305+P351+P338** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
**P301+P330+P331** IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
**P303+P361+P353** IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water / shower.  
**P310** Immediately call a POISON CENTER / doctor / . . .  
**P304+P340** IF INHALED: remove person to fresh air and keep comfortable for breathing.  
**P302+P352** IF ON SKIN: wash with plenty of water / . . .  
**P363** Wash contaminated clothing before reuse.

#### Storage:

- P405** Store locked up.

#### Disposal:

- P501** Dispose of contents / container according to applicable law.

### 2.2. Other hazards

Information not available

### 3. Composition/information on ingredients

#### 3.2. Mixtures

##### Contains:

Identification	x = Conc. %	Classification:
<b>Formaldehyde, polymer with MXDA and phenol</b>		
CAS	57214-10-5 16 ≤ x < 17	Skin corrosion, category 1B H314, Serious eye damage, category 1 H318, Skin sensitization, category 1 H317
EC	500-137-0	
INDEX		
<b>3-AMINOMETHYL 3,5,5-TRIMETHYLCYCLOHEXYLAMINE</b>		
CAS	2855-13-2 5 ≤ x < 6	Acute toxicity, category 4 H302, Acute toxicity, category 4 H312, Skin corrosion, category 1B H314, Serious eye damage, category 1 H318, Skin sensitization, category 1 H317, Hazardous to the aquatic environment, chronic toxicity, category 3 H412
EC	220-666-8	
INDEX	612-067-00-9	
<b>TITANIUM DIOXIDE</b>		
CAS	13463-67-7 4.5 ≤ x < 5	Carcinogenicity, category 2 H351
EC	236-675-5	
INDEX		
<b>POLYETHERAMINE</b>		
CAS	9046-10-0 2.5 ≤ x < 3	Skin corrosion, category 1B H314, Serious eye damage, category 1 H318, Hazardous to the aquatic environment, chronic toxicity, category 3 H412
EC	618-561-0	
INDEX		
<b>BENZYL ALCOHOL</b>		
CAS	100-51-6 2.5 ≤ x < 3	Acute toxicity, category 4 H302, Acute toxicity, category 4 H332
EC	202-859-9	
INDEX	603-057-00-5	
<b>3-Aminopropyltriethoxysilane</b>		
CAS	919-30-2 1.5 ≤ x < 2	Acute toxicity, category 4 H302, Skin corrosion, category 1B H314, Serious eye damage, category 1 H318, Skin sensitization, category 1 H317
EC	213-048-4	
INDEX	612-108-00-0	
<b>METAXYLENDIAMINE</b>		
CAS	1477-55-0 0.7 ≤ x < 1	Acute toxicity, category 4 H302, Acute toxicity, category 4 H332, Skin corrosion, category 1B H314, Serious eye damage, category 1 H318, Skin sensitization, category 1 H317, Hazardous to the aquatic environment, chronic toxicity, category 3 H412
EC	216-032-5	
INDEX		

# Tenax Spa

## DOMOCOMB-B-LIQUID

Revision nr.1  
Dated 10/30/2019  
First compilation  
Printed on 11/6/2020  
Page n. 3 / 12

### 3. Composition/information on ingredients ... / >>

#### AMINOETHYL AMINOPROPYL TRIMETHOXYSILANE

CAS 1760-24-3 0.1 ≤ x < 0.4

Acute toxicity, category 4 H302, Acute toxicity, category 4 H332,  
Serious eye damage, category 1 H318, Skin irritation, category 2 H315,  
Skin sensitization, category 1 H317

EC 217-164-6  
INDEX

\* There is a batch to batch variation.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

### 4. First-aid measures

#### 4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

#### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

### 5. Fire-fighting measures

#### 5.1. Extinguishing media

##### SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

##### UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

#### 5.2. Special hazards arising from the substance or mixture

##### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

#### 5.3. Advice for firefighters

##### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

##### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

### 6. Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

#### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

# Tenax Spa

## DOMOCOMB-B-LIQUID

Revision nr.1  
Dated 10/30/2019  
First compilation  
Printed on 11/6/2020  
Page n. 4 / 12

### 6. Accidental release measures ... / >>

#### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

### 7. Handling and storage

#### 7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

#### 7.3. Specific end use(s)

Information not available

### 8. Exposure controls/personal protection

#### 8.1. Control parameters

Regulatory References:

USA	NIOSH-REL	NIOSH publication No. 2005-149, 3th printing, 2007.
USA	OSHA-PEL	Occupational Exposure Limits - Limits for Air Contaminants TABLE Z-1-1910.1000.
USA	CAL/OSHA-PEL	California Division of Occupational Safety and Health (Cal-OSHA) Permissible Exposure Limits (PELs).
	TLV-ACGIH	ACGIH 2019

#### TITANIUM DIOXIDE

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH	-	10				
OSHA	USA	15				INHAL
CAL/OSHA	USA	10				INHAL
CAL/OSHA	USA	5				RESP

#### METAXYLENDIAMINE

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH	-			0.1		
CAL/OSHA	USA	0.1				SKIN
NIOSH	USA			0.1 (C)		SKIN

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

#### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must comply with current regulations.

##### HAND PROTECTION

Protect hands with category III work gloves (OSHA 29 CFR 1910.138).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends

# Tenax Spa

## DOMOCOMB-B-LIQUID

Revision nr.1  
Dated 10/30/2019  
First compilation  
Printed on 11/6/2020  
Page n. 5 / 12

### 8. Exposure controls/personal protection ... / >>

on the duration and type of use.

#### SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear. Wash body with soap and water after removing protective clothing.

#### EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

#### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84, OSHA 29 CFR 1910.134.

#### ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

### 9. Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	pasty liquid	
Colour	Not available	
Odour	Not available	
Odour threshold	Not available	
pH	Not available	
Melting point / freezing point	Not available	
Initial boiling point	Not available	
Boiling range	Not available	
Flash point	> 93 °C	(199,4 °F)
Evaporation Rate	Not available	
Flammability of solids and gases	Not available	
Lower inflammability limit	Not available	
Upper inflammability limit	Not available	
Lower explosive limit	Not available	
Upper explosive limit	Not available	
Vapour pressure	Not available	
Vapour density	Not available	
Relative density	Not available	
Solubility	Not available	
Partition coefficient: n-octanol/water	Not available	
Auto-ignition temperature	Not available	
Decomposition temperature	Not available	
Viscosity	Not available	
Explosive properties	Not available	
Oxidising properties	Not available	

#### 9.2. Other information

Information not available

### 10. Stability and reactivity

#### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

#### BENZYL ALCOHOL

Decomposes at temperatures above 870°C/1598°F. Possibility of explosion.

#### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

#### 10.3. Possibility of hazardous reactions

# Tenax Spa

## DOMOCOMB-B-LIQUID

Revision nr.1  
Dated 10/30/2019  
First compilation  
Printed on 11/6/2020  
Page n. 6 / 12

### 10. Stability and reactivity ... / >>

No hazardous reactions are foreseeable in normal conditions of use and storage.

#### 3-AMINOMETHYL 3,5,5-TRIMETHYLCYCLOHEXYLAMINE

May react dangerously with: strong oxidising agents, concentrated inorganic acids.

#### BENZYL ALCOHOL

May react dangerously with: hydrobromic acid, iron, oxidising agents, sulphuric acid. Risk of explosion on contact with: phosphorus trichloride.

#### 10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

#### 3-AMINOMETHYL 3,5,5-TRIMETHYLCYCLOHEXYLAMINE

Avoid contact with: strong acids, strong oxidants.

#### BENZYL ALCOHOL

Avoid exposure to: air, sources of heat, naked flames.

#### 10.5. Incompatible materials

#### BENZYL ALCOHOL

Incompatible with: sulphuric acid, oxidising substances, aluminium.

#### 10.6. Hazardous decomposition products

Information not available

### 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

#### 11.1. Information on toxicological effects

##### Metabolism, toxicokinetics, mechanism of action and other information

Information not available

##### Information on likely routes of exposure

Information not available

##### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

##### Interactive effects

Information not available

##### ACUTE TOXICITY

Corrosive to the respiratory tract.

#### TITANIUM DIOXIDE

LD50 (Oral) > 10000 mg/kg Rat

#### BENZYL ALCOHOL

LD50 (Oral) 1230 mg/kg Rat

LD50 (Dermal) 2000 mg/kg Rabbit

LC50 (Inhalation) > 4.1 mg/l/4h Rat

#### POLYETHERAMINE

LD50 (Oral) > 480 mg/kg rat

LD50 (Dermal) > 1560 mg/kg rabbit

#### METAXYLENDIAMINE

LD50 (Oral) 930 mg/kg rat

LD50 (Dermal) > 3100 mg/kg rabbit

LC50 (Inhalation) 1.34 mg/l rat (fog)

##### SKIN CORROSION / IRRITATION

# Tenax Spa

## DOMOCOMB-B-LIQUID

Revision nr.1  
Dated 10/30/2019  
First compilation  
Printed on 11/6/2020  
Page n. 7 / 12

### 11. Toxicological information ... / >>

Corrosive for the skin

#### SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

#### RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

#### GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

#### CARCINOGENICITY

Suspected of causing cancer

Carcinogenicity Assessment:  
13463-67-7 TITANIUM DIOXIDE  
ACGIH:: A4  
IARC:2B

#### REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

#### STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

#### STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

#### ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

### 12. Ecological information

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

#### 12.1. Toxicity

##### POLYETHERAMINE

LC50 - for Fish	> 464 mg/l/96h <i>Leuciscus idus</i>
EC50 - for Crustacea	15 mg/l/48h <i>Daphnia magna</i>
EC10 for Algae / Aquatic Plants	450 mg/l/72h <i>Pseudomonas putida</i>

##### METAXYLENDIAMINE

LC50 - for Fish	87.6 mg/l/96h <i>oryzias latipes</i>
EC50 - for Crustacea	15.2 mg/l/48h <i>daphnia magna</i>
EC50 - for Algae / Aquatic Plants	20.3 mg/l/72h <i>selenastrum capricornutum</i>
Chronic NOEC for Crustacea	4.7 mg/l 21d
Chronic NOEC for Algae / Aquatic Plants	10.5 mg/l 72 h

# Tenax Spa

## DOMOCOMB-B-LIQUID

Revision nr.1  
Dated 10/30/2019  
First compilation  
Printed on 11/6/2020  
Page n. 8 / 12

### 12. Ecological information ... / >>

#### 12.2. Persistence and degradability

##### TITANIUM DIOXIDE

Solubility in water < 0.001 mg/l

Degradability: information not available

##### BENZYL ALCOHOL

Rapidly degradable

##### 3-AMINOMETHYL 3,5,5-TRIMETHYLCYCLOHEXYLAMINE

Solubility in water 1000 - 10000 mg/l

NOT rapidly degradable

##### POLYETHERAMINE

NOT rapidly degradable

##### METAXYLENDIAMINE

Entirely degradable

#### 12.3. Bioaccumulative potential

##### BENZYL ALCOHOL

Partition coefficient: n-octanol/water 1.1

#### 12.4. Mobility in soil

Information not available

#### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

#### 12.6. Other adverse effects

Information not available

### 13. Disposal considerations

#### 13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

##### CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

### 14. Transport information

#### 14.1. UN number

ADR / RID, IMDG, IATA: 2735

#### 14.2. UN proper shipping name

ADR / RID: AMINES, LIQUID, CORROSIVE, N.O.S. (REACTION PRODUCT: 4-TERT-BUTYLPHENOL - METAXYLENEDIAMINE; 3-AMINOMETHYL 3,5,5-TRIMETHYLCYCLOHEXYLAMINE)

IMDG: AMINES, LIQUID, CORROSIVE, N.O.S. (REACTION PRODUCT: 4-TERT-BUTYLPHENOL - METAXYLENEDIAMINE; 3-AMINOMETHYL 3,5,5-TRIMETHYLCYCLOHEXYLAMINE)

IATA: AMINES, LIQUID, CORROSIVE, N.O.S. (REACTION PRODUCT: 4-TERT-BUTYLPHENOL - METAXYLENEDIAMINE; 3-AMINOMETHYL 3,5,5-TRIMETHYLCYCLOHEXYLAMINE)



# Tenax Spa

## DOMOCOMB-B-LIQUID

Revision nr.1  
Dated 10/30/2019  
First compilation  
Printed on 11/6/2020  
Page n. 9 / 12

### 14. Transport information ... / >>

#### 14.3. Transport hazard class(es)

ADR / RID: Class: 8 Label: 8



IMDG: Class: 8 Label: 8



IATA: Class: 8 Label: 8



#### 14.4. Packing group

ADR / RID, IMDG, IATA: II

#### 14.5. Environmental hazards

ADR / RID: NO

IMDG: NO

IATA: NO

#### 14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 80	Limited Quantities: 1 L	Tunnel restriction code: (E)
	Special Provision: -		
IMDG:	EMS: F-A, S-B	Limited Quantities: 1 L	
IATA:	Cargo:	Maximum quantity: 30 L	Packaging instructions: 855
	Pass.:	Maximum quantity: 1 L	Packaging instructions: 851
	Special Instructions:	A3, A803	

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

### 15. Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

U.S. Federal Regulations

TSCA:

All components are listed on TSCA Inventory.

Clean Air Act Section 112(b):

25322-68-3 POLYETHYLENGLYCOL (Glycol ethers)

Clean Air Act Section 602 Class I Substances:

No component(s) listed.

Clean Air Act Section 602 Class II Substances:

No component(s) listed.

Clean Water Act – Priority Pollutants:

No component(s) listed.

Clean Water Act – Toxic Pollutants:

No component(s) listed.

DEA List I Chemicals (Precursor Chemicals):

No component(s) listed.

DEA List II Chemicals (Essential Chemicals):

# Tenax Spa

## DOMOCOMB-B-LIQUID

Revision nr.1  
Dated 10/30/2019  
First compilation  
Printed on 11/6/2020  
Page n. 10 / 12

### 15. Regulatory information ... />>

No component(s) listed.

EPA List of Lists:

313 Category Code:

25322-68-3 POLYETHYLENGLYCOL (Glycol ethers)

EPCRA 302 EHS TPQ:

No component(s) listed.

EPCRA 304 EHS RQ:

No component(s) listed.

CERCLA RQ:

No component(s) listed.

EPCRA 313 TRI:

25322-68-3 POLYETHYLENGLYCOL (Glycol ethers)

RCRA Code:

No component(s) listed.

CAA 112 (r) RMP TQ:

No component(s) listed.

State Regulations

Massachussetts:

13463-67-7 TITANIUM DIOXIDE (Titanium dioxide (airborne, unbound particles of respirable size))  
100-51-6 BENZYL ALCOHOL  
1477-55-0 METAXYLENDIAMINE

Minnesota:

13463-67-7 TITANIUM DIOXIDE (Titanium dioxide (airborne, unbound particles of respirable size))  
100-51-6 BENZYL ALCOHOL  
25322-68-3 POLYETHYLENGLYCOL (Glycol ethers)  
1477-55-0 METAXYLENDIAMINE

New Jersey:

2855-13-2 3-AMINOMETHYL 3,5,5-TRIMETHYLCYCLOHEXYLAMINE  
13463-67-7 TITANIUM DIOXIDE (Titanium dioxide (airborne, unbound particles of respirable size))  
25322-68-3 POLYETHYLENGLYCOL (Glycol ethers)  
25322-68-3 POLYETHYLENGLYCOL (Glycol ethers)  
1477-55-0 METAXYLENDIAMINE

New York:

No component(s) listed.

Pennsylvania:

13463-67-7 TITANIUM DIOXIDE (Titanium dioxide (airborne, unbound particles of respirable size))  
100-51-6 BENZYL ALCOHOL  
1477-55-0 METAXYLENDIAMINE

California:

1477-55-0 METAXYLENDIAMINE

Proposition 65:

**WARNING!** This product contains chemicals known to the State of California to cause cancer and birth defects or reproductive harm.

13463-67-7 TITANIUM DIOXIDE C (Titanium dioxide (airborne, unbound particles of respirable size))

International Regulations

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

# Tenax Spa

## DOMOCOMB-B-LIQUID

Revision nr.1  
Dated 10/30/2019  
First compilation  
Printed on 11/6/2020  
Page n. 11 / 12

### 15. Regulatory information ... / >>

Candadian WHMIS  
Information not available

### 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>H351</b>	Suspected of causing cancer.
<b>H302</b>	Harmful if swallowed.
<b>H312</b>	Harmful in contact with skin.
<b>H332</b>	Harmful if inhaled.
<b>H314</b>	Causes severe skin burns and eye damage.
<b>H318</b>	Causes serious eye damage.
<b>H315</b>	Causes skin irritation.
<b>H317</b>	May cause an allergic skin reaction.
<b>H412</b>	Harmful to aquatic life with long lasting effects.

#### LEGEND:

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAA 112 @ RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112@)
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: EC Regulation 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

#### GENERAL BIBLIOGRAPHY:

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh - Registry of Toxic Effects of Chemical Substances
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy
  
- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Communication Standard (HCS 2012)
- IARC website

# Tenax Spa

## DOMOCOMB-B-LIQUID

Revision nr.1  
Dated 10/30/2019  
First compilation  
Printed on 11/6/2020  
Page n. 12 / 12

- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112© of the Clean Air Act- Massachussetts 105 CMR Department of public health 670.000: "Right to Know"
- Minensota Chapter 5206 Departemnt Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

#### CALCULATION METHODS FOR CLASSIFICATION

Product classification derives from criteria established by the OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200), unless determined otherwise in Section 11 and 12. The data for evaluation of chemical-physical properties are reported in section 9.