Revision nr.7 Dated 8/3/2023

Printed on 9/20/2023
Page n. 1 / 14
Replaced revision:6 (Dated 10/10/2022)

ΕN

Safety Data Sheet

According to U.S.A. Federal Hazcom 2012

1. Identification

1.1. Product identifier

STRONGEDGE-B-XPRESS Code: Product name STRONGEDGE PARTE B XPRESS

1.2. Relevant identified uses of the substance or mixture and uses advised against

LIQUID EPOXY RESIN FOR STONES.

Identified Uses	Industrial	Professional	Consumer
ADHESIVE SYSTEM/TREATMENT FOR STONE			
SECTOR	\checkmark	\checkmark	-

1.3. Details of the supplier of the safety data sheet

TENAX SPA Name Via I Maggio, 226 Full address (VR) **District and Country** 37020 Volargne Italy +39 045 6887593 Tel +39 045 6862456 Fax

e-mail address of the competent person responsible for the Safety Data Sheet

Supplier: **Tenax Usa**

7606 Whitehall Executive Center Drive Suite 400, 28273 Charlotte NC, US

May damage fertility or the unborn child.

Causes severe skin burns and eye damage.

Harmful if swallowed.

Causes serious eye damage.

May cause an allergic skin reaction.

Tel. 001 7045831173 - Fax 001 7045833166

info@tenaxusa.com

msds@tenax.it

1.4. Emergency telephone number

For urgent inquiries refer to Infotrac

US and Canada: 1-800-535-5053

Int'l: 1-352-323-3500 info@infotrac.net

2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200). The product thus requires a safety datasheet.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Classification and Hazard Statement

Reproductive toxicity, category 1B Acute toxicity, category 4 Skin corrosion, category 1 Serious eye damage, category 1 Skin sensitization, category 1A

Hazard pictograms:



Danger Signal words:

Hazard statements:

H360 May damage fertility or the unborn child.

@EPY 11.5.1 - SDS 1004.14



TENAX SPA

STRONGEDGE PARTE B XPRESS

Revision nr.7 Dated 8/3/2023 Printed on 9/20/2023 Page n. 2 / 14

Page n. 2 / 14 Replaced revision:6 (Dated 10/10/2022)

2. Hazards identification .../>>

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.H317 May cause an allergic skin reaction.

Precautionary statements:

Prevention:

P260 Do not breathe dust / fume / gas / mist / vapours / spray.

P202 Do not handle until all safety precautions have been read and understood.

P201 Obtain special instructions before use.

P280 Wear protective gloves/ protective clothing / eye protection / face protection.

P270 Do not eat, drink or smoke when using this product.

P264 Wash the hands thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

Response:

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water / shower.

P310 Immediately call a POISON CENTER / doctor if you feel unwell.

P304+P340 IF INHALED: remove person to fresh air and keep comfortable for breathing.

P330 Rinse mouth.

P302+P352 IF ON SKIN: wash with plenty of water / . . .

P301+P312 IF SWALLOWED: Call a POISON CENTER / doctor / . . . / if you feel unwell.

P363 Wash contaminated clothing before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents / container according to applicable law.

2.2. Other hazards

Environmental classification as for Reg. (EC) 1272/2008 (CLP):

The product is classified as hazardous for environment pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP).

Classification and Hazard Statement

Hazardous to the aquatic environment, acute toxicity, category 1 Very toxic to aquatic life.

Hazardous to the aquatic environment, chronic toxicity, category 1 Very toxic to aquatic life with long lasting effects.

Hazard pictograms:



Signal words: Warning

Hazard statements:

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements:

Prevention:

P273 Avoid release to the environment.

Response:

P391 Collect spillage.

Storage:

Disposal:

P501 Dispose of contents / container according to applicable law.

Additional hazards Information not available



Revision nr.7 Dated 8/3/2023 Printed on 9/20/2023 Page n. 3 / 14 Replaced revision:6 (Dated 10/10/2022)

3. Composition/information on ingredients

3.2. Mixtures

Contains:

Classification: Identification x = Conc. %

1,3-BIS(AMINOMETHYL)CYCLOHEXANE

 $40 \le x < 42$ Acute toxicity, category 4 H302, Acute toxicity, category 4 H312, Skin

> corrosion, category 1A H314, Serious eye damage, category 1 H318, Hazardous to the aquatic environment, chronic toxicity, category 3 H412

EC 219-941-5 CAS 2579-20-6 REACH Reg. 01-2119543741-41

BENZYL ALCOHOL

INDEX 603-057-00-5 $15 \le x < 16$

FC 202-859-9 100-51-6 CAS REACH Reg. 01-2119492630-38

4-NONYLPHENOL, BRANCHED

INDEX 601-053-00-8 $14.5 \le x < 15.5$ Reproductive toxicity, category 2 H361, Acute toxicity, category 4 H302,

Acute toxicity, category 4 H302, Acute toxicity, category 4 H332

Skin corrosion, category 1B H314, Serious eye damage, category 1 H318, Hazardous to the aquatic environment, acute toxicity, category 1 H400 M=10, Hazardous to the aquatic environment, chronic toxicity, category 1

H410 M=10

EC 284-325-5 CAS 84852-15-3 REACH Reg. 01-2119510715-45 4,4'-ISOPROPYLIDENEDIPHENOL

INDEX 604-030-00-0 $9.5 \le x < 10.5$ Reproductive toxicity, category 1B H360, Serious eve damage, category 1 H318, Specific target organ toxicity - single exposure, category 3 H335, Skin

sensitization, category 1 H317, Hazardous to the aquatic environment, acute toxicity, category 1 H400 M=1, Hazardous to the aquatic environment,

chronic toxicity, category 1 H410 M=10

EC 201-245-8 80-05-7 CAS

REACH Reg. 01-2119457856-23

3-AMINOMETHYL 3.5.5-TRIMETHYLCYCLOHEXYLAMINE

INDEX 612-067-00-9 $1.5 \le x < 2$

Acute toxicity, category 4 H302, Skin corrosion, category 1B H314, Serious eye damage, category 1 H318, Skin sensitization, category 1A H317,

Hazardous to the aquatic environment, chronic toxicity, category 3 H412

EC 220-666-8 CAS 2855-13-2 REACH Reg. 01-2119514687-32

N-(3-(TRIMETHOXYSILYL)PROPYL)ETHYLENEDIAMINE

 $0.4 \le x < 0.7$

Serious eye damage, category 1 H318, Specific target organ toxicity - single

exposure, category 3 H335, Skin sensitization, category 1 H317

EC 217-164-6 CAS 1760-24-3 REACH Reg. 01-2119970215-39

TRIS (4-NONYLPHENOL, BRANCHED) PHOSPHITE

 $0.4 \le x < 0.7$

Skin irritation, category 2 H315, Skin sensitization, category 1 H317, Hazardous to the aquatic environment, acute toxicity, category 1 H400 M=1, Hazardous to the aquatic environment, chronic toxicity, category 1 H410

EC 701-028-2

CAS

REACH Reg. 01-2119520601-54-XXXX

* There is a batch to batch variation.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

@EPY 11.5.1 - SDS 1004.14



TENAX SPA STRONGEDGE PARTE B XPRESS

Revision nr.7 Dated 8/3/2023 Printed on 9/20/2023 Page n. 4 / 14 Replaced revision:6 (Dated 10/10/2022)

4. First-aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

5. Fire-fighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

1,3-BIS(AMINOMETHYL)CYCLOHEXANE

Nitrogen oxides (NOx), carbon monoxide (CO), carbon dioxide (CO2), pyrolysis products.

Combustion products: mainly COx and NOx.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point



TENAX SPA STRONGEDGE PARTE B XPRESS

Revision nr.7 Dated 8/3/2023 Printed on 9/20/2023 Page n. 5 / 14 Replaced revision:6 (Dated 10/10/2022)

6. Accidental release measures .../>>

13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

FU **OEL EU** Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.

4,4'-ISOPROPYLIDENEDIPHENOL										
Threshold Limit	t Value									
Type	Country	TWA/8h		STEL/15min		Remarks / Observations				
		mg/m3	ppm	mg/m3	ppm					
OEL	EU	2				INHAL				

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must comply with current regulations.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (OSHA 29 CFR 1910.138): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear. Wash body with soap and water after removing protective clothing. **EYE PROTECTION**

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84, OSHA 29 CFR 1910.134.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure



TENAX SPA STRONGEDGE PARTE B XPRESS

Revision nr.7 Dated 8/3/2023 Printed on 9/20/2023 Page n. 6 / 14 Replaced revision:6 (Dated 10/10/2022)

8. Exposure controls/personal protection .../>>

compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

HAND PROTECTION: Protect hands with work gloves for protection from chemical agents in nitrile or fluoroelastomer (EN 374-1: 2016) at least type B or higher based on the risk assessment carried out by the company. Breakthrough time> 480 minutes.

Material thickness:

NITRILE short contact> 0.38 mm prolonged contact> 0.55 mm FLUOROELASTOMER short contact> 0.50 mm

prolonged contact> 1.50 mm

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

PropertiesValueInformationAppearanceviscous liquidColourtransparent

Odour characteristic
Odour threshold not available
pH 10
Melting point / freezing point not available
Initial boiling point not available
Boiling range not available

Flash point > 93 °C (199,4 °F)

not available Evaporation rate Flammability not available not available Lower inflammability limit Upper inflammability limit not available not available Lower explosive limit Upper explosive limit not available Vapour pressure not available Vapour density not available Relative density g/cm3

Solubility partially soluble in water

Partition coefficient: n-octanol/water not available
Auto-ignition temperature not available
Decomposition temperature not available
Viscosity not available
Explosive properties not available
Oxidising properties not available

9.2. Other information

VOC: 15,98 % - 159,84 g/litre

10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

BENZYL ALCOHOL

Decomposes at temperatures above 870°C/1598°F.Possibility of explosion.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

BENZYL ALCOHOL

May react dangerously with: hydrobromic acid,iron,oxidising agents,sulphuric acid.Risk of explosion on contact with: phosphorus trichloride.

3-AMINOMETHYL 3,5,5-TRIMETHYLCYCLOHEXYLAMINE

May react dangerously with: strong oxidising agents, concentrated inorganic acids.



TENAX SPA STRONGEDGE PARTE B XPRESS

Revision nr.7 Dated 8/3/2023 Printed on 9/20/2023 Page n. 7 / 14 Replaced revision:6 (Dated 10/10/2022)

10. Stability and reactivity .../>>

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

1,3-BIS(AMINOMETHYL)CYCLOHEXANE

Avoid exposure to: sources of heat,naked flames,overheated surfaces,ignition sources.

BENZYL ALCOHOL

Avoid exposure to: air,sources of heat,naked flames. 3-AMINOMETHYL 3,5,5-TRIMETHYLCYCLOHEXYLAMINE

Avoid contact with: strong acids, strong oxidants.

10.5. Incompatible materials

1,3-BIS(AMINOMETHYL)CYCLOHEXANE

acids,reducing agents,oxidising agents.

BENZYL ALCOHOL

Incompatible with: sulphuric acid,oxidising substances,aluminium.

10.6. Hazardous decomposition products

Information not available

11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

1,3-BIS(AMINOMETHYL)CYCLOHEXANE

LD50 (Oral): 700 mg/kg ratto
LD50 (Dermal): 1700 mg/kg coniglio

4-NONYLPHENOL, BRANCHED

LD50 (Oral): 1620 mg/kg rat LD50 (Dermal): 2140 mg/kg rabbit

BENZYL ALCOHOL

 LD50 (Oral):
 1230 mg/kg Rat

 LD50 (Dermal):
 2000 mg/kg Rabbit

 LC50 (Inhalation vapours):
 > 4.1 mg/l/4h Rat

3-AMINOMETHYL 3,5,5-TRIMETHYLCYCLOHEXYLAMINE

 LD50 (Oral):
 1030 mg/kg Ratto

 LD50 (Dermal):
 > 2000 mg/kg Ratto

 LC50 (Inhalation mists/powders):
 > 5.01 mg/l/4h Ratto

4,4'-ISOPROPYLIDENEDIPHENOL

LD50 (Oral): 5000 mg/kg LD50 (Dermal): 3000 mg/kg Rabbit



Revision nr.7 Dated 8/3/2023 Printed on 9/20/2023 Page n. 8 / 14

Page n. 8 / 14 Replaced revision:6 (Dated 10/10/2022) ΕN

11. Toxicological information .../>>

N-(3-(TRIMETHOXYSILYL)PROPYL)ETHYLENEDIAMINE

 LD50 (Oral):
 2295 mg/kg Ratto

 LD50 (Dermal):
 > 2000 mg/kg Coniglio

 LC50 (Inhalation mists/powders):
 1.49 mg/l/4h Ratto

TRIS (4-NONYLPHENOL, BRANCHED) PHOSPHITE

LD50 (Oral): > 2000 mg/kg ratto
LD50 (Dermal): > 2000 mg/kg coniglio

SKIN CORROSION / IRRITATION

Corrosive for the skin

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

May damage fertility or the unborn child

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

12. Ecological information

This product is dangerous for the environment and highly toxic for aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity

1,3-BIS(AMINOMETHYL)CYCLOHEXANE

LC50 - for Fish 130 mg/l/96h leuciscus idus

EC50 - for Crustacea 65.4 mg/l/48h daphnia magna

EC50 - for Algae / Aquatic Plants 90 mg/l/72h pseudomonas putida

Chronic NOEC for Algae / Aquatic Plants 14.4 mg/l Pseudokirchneriella subcapitata

4-NONYLPHENOL, BRANCHED

LC50 - for Fish 0.017 mg/l/96h marine water fish

EC50 - for Crustacea 0.051 mg/l/48h marine invertebrates

EPY 11.5.1 - SDS 1004.14

Tenax

TENAX SPA STRONGEDGE PARTE B XPRESS

Revision nr.7 Dated 8/3/2023 Printed on 9/20/2023 Page n. 9 / 14 Replaced revision:6 (Dated 10/10/2022) ΕN

12. Ecological information .../>>

EC50 - for Algae / Aquatic Plants 0.027 mg/l/72h marine water algae

Chronic NOEC for Fish 0.00046 mg/l marine water fish

Chronic NOEC for Crustacea 0.00946 mg/l marine invertebrates

Chronic NOEC for Algae / Aquatic Plants 0.5 mg/l marine water algae

BENZYL ALCOHOL

LC50 - for Fish 460 mg/l/96h Pimephales promelas

EC50 - for Crustacea 230 mg/l/48h Daphnia magna

EC50 - for Algae / Aquatic Plants 770 mg/l/72h Pseudokirchneriella subcapitata

Chronic NOEC for Crustacea 51 mg/l Daphnia magna

3-AMINOMETHYL 3,5,5-TRIMETHYLCYCLOHEXYLAMINE

LC50 - for Fish 110 mg/l/96h Leuciscus idus

EC50 - for Crustacea 23 mg/l/48h Daphnia magna

EC50 - for Algae / Aquatic Plants > 50 mg/l/72h Scenedesmus subspicatus

EC10 for Algae / Aquatic Plants 11.2 mg/l/72h Scenedesmus subspicatus

Chronic NOEC for Crustacea 3 mg/l 21 d

4,4'-ISOPROPYLIDENEDIPHENOL

LC50 - for Fish 9.4 mg/l/96h Menidia menidia

EC50 - for Crustacea 10.2 mg/l/48h Daphnia magna

TRIS (4-NONYLPHENOL, BRANCHED) PHOSPHITE

LC50 - for Fish 7.1 mg/l/96h pesce zebra

EC50 - for Crustacea 0.42 mg/l/48h daphnia magna

LC10 for Fish 44 mg/l/28d

12.2. Persistence and degradability

1,3-BIS(AMINOMETHYL)CYCLOHEXANE Degradability: information not available

4-NONYLPHENOL, BRANCHED

Rapidly degradable

BENZYL ALCOHOL Rapidly degradable

3-AMINOMETHYL 3,5,5-TRIMETHYLCYCLOHEXYLAMINE

Solubility in water 1000 - 10000 mg/l

NOT rapidly degradable

4,4'-ISOPROPYLIDENEDIPHENOL

Solubility in water 301 mg/l

Rapidly degradable

12.3. Bioaccumulative potential

©EPY 11.5.1 - SDS 1004.14



TENAX SPA STRONGEDGE PARTE B XPRESS

Revision nr.7 Dated 8/3/2023 Printed on 9/20/2023 Page n. 10 / 14 Replaced revision:6 (Dated 10/10/2022)

12. Ecological information .../>>

1,3-BIS(AMINOMETHYL)CYCLOHEXANE

Partition coefficient: n-octanol/water 0.783

4-NONYLPHENOL, BRANCHED

Partition coefficient: n-octanol/water 5.4

BCF > 260

BENZYL ALCOHOL

Partition coefficient: n-octanol/water 1.1

4,4'-ISOPROPYLIDENEDIPHENOL

Partition coefficient: n-octanol/water 3.4

12.4. Mobility in soil

4-NONYLPHENOL, BRANCHED

Partition coefficient: soil/water > 22

4,4'-ISOPROPYLIDENEDIPHENOL

Partition coefficient: soil/water 2.95

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Other adverse effects

Information not available

13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

14. Transport information

14.1. UN number

ADR / RID, IMDG, IATA: 1760

14.2. UN proper shipping name

ADR / RID: CORROSIVE LIQUID, N.O.S. (1,3-BIS(AMINOMETHYL)CYCLOHEXANE; 4-NONYLPHENOL, BRANCHED)
IMDG: CORROSIVE LIQUID, N.O.S. (1,3-BIS(AMINOMETHYL)CYCLOHEXANE; 4-NONYLPHENOL, BRANCHED)
IATA: CORROSIVE LIQUID, N.O.S. (1,3-BIS(AMINOMETHYL)CYCLOHEXANE; 4-NONYLPHENOL, BRANCHED)

Revision nr.7 Dated 8/3/2023 Printed on 9/20/2023 Page n. 11 / 14 Replaced revision:6 (Dated 10/10/2022)

ΕN

14. Transport information .../>>

14.3. Transport hazard class(es)

ADR / RID:

Class: 8

Label: 8

IMDG:

Class: 8

Label: 8

IATA:

Class: 8

Label: 8



14.4. Packing group

ADR / RID, IMDG, IATA:

14.5. Environmental hazards

ADR / RID:

Environmentally Hazardous

IMDG:

Marine Pollutant

IATA:

NO

For Air transport, environmentally hazardous mark is only mandatory for UN 3077 and UN 3082.

14.6. Special precautions for user ADR / RID:

HIN - Kemler: 80

Limited Quantities: 1 L

Tunnel restriction code: (E)

Packaging instructions: 855

IMDG: IATA:

Special provision: -EMS: F-A, S-B

Limited Quantities: 1 L Maximum quantity: 30 L

Cargo: Passengers:

Maximum quantity: 1 L

Packaging instructions: 851

Special provision:

A3, A803

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

U.S. Federal Regulations

TSCA:

All components of this product are listed on US Toxic Substances Control Act (TSCA) Inventory or are exempt from the listing / notification requirements.

Clean Air Act Section 112(b):

No component(s) listed.

Clean Air Act Section 602 Class I Substances:

No component(s) listed.

Clean Air Act Section 602 Class II Substances:

No component(s) listed.

Clean Water Act - Priority Pollutants:

No component(s) listed.



TENAX SPA STRONGEDGE PARTE B XPRESS

Revision nr.7 Dated 8/3/2023 Printed on 9/20/2023 Page n. 12 / 14 Replaced revision:6 (Dated 10/10/2022)

15. Regulatory information .../>>

Clean Water Act – Toxic Pollutants:

No component(s) listed.

DEA List I Chemicals (Precursor Chemicals):

No component(s) listed.

DEA List II Chemicals (Essential Chemicals):

No component(s) listed.

EPA List of Lists:

313 Category Code:

4,4'-ISOPROPYLIDENEDIPHENOL (Phenols) 80-05-7

EPCRA 302 EHS TPQ:

No component(s) listed.

EPCRA 304 EHS RQ:

No component(s) listed.

CERCLA RQ:

No component(s) listed.

EPCRA 313 TRI:

4,4'-ISOPROPYLIDENEDIPHENOL (Phenols) 80-05-7

RCRA Code:

No component(s) listed.

CAA 112 (r) RMP TQ:

No component(s) listed.

State Regulations

Massachussetts:

100-51-6 BENZYL ALCOHOL

80-05-7 4,4'-ISOPROPYLIDENEDIPHENOL (Phenols)

Minnesota:

100-51-6 BENZYL ALCOHOL

New Jersey:

2855-13-2 3-AMINOMETHYL 3,5,5-TRIMETHYLCYCLOHEXYLAMINE

80-05-7 4,4'-ISOPROPYLIDENEDIPHENOL (Phenols)

New York:

No component(s) listed.

Pennsylvania:

100-51-6 BENZYL ALCOHOL

80-05-7 4,4'-ISOPROPYLIDENEDIPHENOL (Phenols)

California:

80-05-7 4,4'-ISOPROPYLIDENEDIPHENOL (Phenols)

Proposition 65:

This product does not contain any substances know to the State of California to cause cancer, reproductive harm or birth defects.

International Regulations

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

4-NONYLPHENOL, BRANCHED - (NONYLPHENOLS)

Substances subject to the Rotterdam Convention:

Substances subject to the Stockholm Convention:

None



TENAX SPA

STRONGEDGE PARTE B XPRESS

Revision nr.7 Dated 8/3/2023 Printed on 9/20/2023 Page n. 13 / 14

Page n. 13 / 14
Replaced revision:6 (Dated 10/10/2022)

16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

H360 May damage fertility or the unborn child.
H361 Suspected of damaging fertility or the unborn child.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.
H315 Causes skin irritation.
H335 May cause respiratory irritation.
H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H412 Harmful to aquatic life with long lasting effects.

LEGEND:

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAA 112 ® RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112®)
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: Regulation (EC) 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REACH: Regulation (EC) 1907/2006
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

GENERAL BIBLIOGRAPHY:

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh Registry of Toxic Effects of Chemical Substances
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy
- 6 NYCRR part 597
- Cal/OSHA website



TENAX SPA STRONGEDGE PARTE B XPRESS

Revision nr.7 Dated 8/3/2023 Printed on 9/20/2023 Page n. 14 / 14 Replaced revision:6 (Dated 10/10/2022)

16. Other information .../>>

- California Safe Drinking Water and Toxic Enforcement Act
- FPA website
- Hazard Comunication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112® of the Clean Air Act
- Massachussetts 105 CMR Department of public health 670.000: "Right to Know"
- Minensota Chapter 5206 Departemnt Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens. 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Product classification derives from criteria established by the OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200), unless determined otherwise in Section 11 and 12. The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review:

The following sections were modified:

01 / 03 / 05 / 11.