Printed on 11/6/2020 Page n. 1 / 10 Replaced revision:1 (Dated 5/7/2015)

Safety Data Sheet

According to U.S.A. Federal Hazcom 2012

1. Identification

1.1. Product identifier

Product name **TEBLOSSOM REAGENT 1**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Stain remover

Identified Uses	Indust	rial	Professional	Consumer		
ADHESIVE SYSTEM/TREATMENT FOR STONE						
SECTOR	-		\checkmark	-		
1.3. Details of the supplier of the safety data sheet						
Name	Tenax Spa					
Full address	Via I N	laggio, 226				
District and Country	37020	Volargne		(VR)		
•		Italy				
	Tel.	+39 045 6887593				
	Fax	+39 045 6862456				
e-mail address of the competent person						

responsible for the Safety Data Sheet

msds@tenax.it

Product distribution by: **Tenax Usa**

7606 Whitehall Executive Center Drive Suite 400, 28273 Charlotte NC, US

Tel. 001 7045831173 - Fax 001 7045833166

info@tenaxusa.com

1.4. Emergency telephone number

For urgent inquiries refer to Infotrac

US and Canada: 1-800-535-5053

Int'l: 1-352-323-3500 info@infotrac.net

2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200). The product thus requires a safety datasheet.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Classification and Hazard Statement Skin corrosion, category 1

Serious eye damage, category 1

Causes severe skin burns and eye damage.

Causes serious eye damage.

Hazard pictograms:



Signal words: Danger

Hazard statements:

Causes severe skin burns and eye damage. H314

Precautionary statements:

Revision nr.2 Dated 10/9/2019 Printed on 11/6/2020 Page n. 2 / 10 Replaced revision:1 (Dated 5/7/2015)

2. Hazards identification .../>>

Prevention:

P260 Do not breathe dust / fume / gas / mist / vapours / spray.

P280 Wear protective gloves/ protective clothing / eye protection / face protection.

P264 Wash the hands thoroughly after handling.

Response:

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water / shower.

P310 Immediately call a POISON CENTER / doctor / . . .

P304+P340 IF INHALED: remove person to fresh air and keep comfortable for breathing.

P363 Wash contaminated clothing before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents / container according to applicable law.

2.2. Other hazards

Information not available

3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification Conc. % Classification:

HYDROGEN PEROXIDE SOLUTION

CAS 7722-84-1 6 Oxidising liquid, category 1 H271, Acute toxicity, category 4 H302, Acute toxicity,

category 4 H332, Skin corrosion, category 1A H314, Serious eye damage,

category 1 H318, Specific target organ toxicity - single exposure, category 3 H335

EC 231-765-0 INDEX 008-003-00-9

The full wording of hazard (H) phrases is given in section 16 of the sheet.

4. First-aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

5. Fire-fighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

@EPY 9.11.0 - SDS 1004.13

Revision nr.2 Dated 10/9/2019 Printed on 11/6/2020 Page n. 3 / 10 Replaced revision:1 (Dated 5/7/2015)

5. Fire-fighting measures .../>>

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIREDo not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

7. Handling and storage

7.1. Precautions for safe handling

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

USA NIOSH-REL NIOSH publication No. 2005-149, 3th printing, 2007.

USA OSHA-PEL Occupational Exposure Limits - Limits for Air Contaminants TABLE Z-1-1910.1000.

USA CAL/OSHA-PEL California Division of Occupational Safety and Health (Cal-OSHA) Permissible Exposure Limits

(PELs).

TLV-ACGIH ACGIH 2019

Revision nr.2 Dated 10/9/2019 Printed on 11/6/2020 Page n. 4 / 10 Replaced revision:1 (Dated 5/7/2015)

8. Exposure controls/personal protection .../>>

HYDROGEN PEROXIDE SOLUTION										
Threshold Limit Value										
Type	Country	TWA/8h		STEL/15	5min					
		mg/m3	ppm	mg/m3	ppm					
TLV-ACGIH	-	1.4	1							
OSHA	USA	1.4	1							
CAL/OSHA	USA	1.4	1							
NIOSH	USA	1.4	1							

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must comply with current regulations.

HAND PROTECTION

Protect hands with category III work gloves (OSHA 29 CFR 1910.138).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear. Wash body with soap and water after removing protective clothing. EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84, OSHA 29 CFR 1910.134.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties		Value				Information
Appearance		liquid				
Colour		colour	less			
Odour		odour	less			
Odour threshold		Not av	/ailable			
pH		3,4-4,0				
Melting point / freezing point		Not available				
Initial boiling point		100	°C	(212 °F)		
Boiling range		Not av	/ailable			
Flash point	>	93	°C		(199,4 °F)	
Evaporation Rate		Not av	/ailable			
Flammability of solids and gases		Not av	/ailable			
Lower inflammability limit		Not av	/ailable			
Upper inflammability limit		Not av	/ailable			
Lower explosive limit		Not av	/ailable			
Upper explosive limit		Not av	/ailable			
Vapour pressure		22	mmHg			
Vapour density		Not av	/ailable			
Relative density		1.07				
Solubility		solubl	e in water			
Partition coefficient: n-octanol/water		Not av	/ailable			
Auto-ignition temperature		Not av	/ailable			
Decomposition temperature		Not av	/ailable			
Viscosity		Not av	/ailable			
Explosive properties		Not av	/ailable			

Revision nr.2 Dated 10/9/2019 Printed on 11/6/2020 Page n. 5 / 10 Replaced revision:1 (Dated 5/7/2015)

9. Physical and chemical properties .../>>

Oxidising properties

Not available

9.2. Other information

Information not available

10. Stability and reactivity

10.1. Reactivity

HYDROGEN PEROXIDE SOLUTION

Decomposes if exposed to: light, heat. Decomposes on contact with: alkaline metals. Possibility of explosion.

10.2. Chemical stability

Information not available

10.3. Possibility of hazardous reactions

The product may react violently with water.

10.4. Conditions to avoid

Avoid overheating. Prevent moisture or water from penetrating inside the containers.

HYDROGEN PEROXIDE SOLUTION

Avoid exposure to: light, heat. Avoid contact with: alkaline substances.

10.5. Incompatible materials

HYDROGEN PEROXIDE SOLUTION

Incompatible with: flammable substances, acetone, ethanol, glycerol, organic sulphides, hydrated bases, oxidising substances, iron, copper, bronze, chromium, zinc, lead, silver, manganese, acetic acid.

10.6. Hazardous decomposition products

Information not available

11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

HYDROGEN PEROXIDE SOLUTION LD50 (Oral)

1193 mg/kg Rat at the concentration of 35%

SKIN CORROSION / IRRITATION

Corrosive for the skin

Revision nr.2 Dated 10/9/2019 Printed on 11/6/2020 Page n. 6 / 10 Replaced revision:1 (Dated 5/7/2015)

11. Toxicological information .../>>

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

Carcinogenicity Assessment:

7722-84-1 HYDROGEN PEROXIDE SOLUTION

ACGIH:: A3 IARC:3

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

Information not available

12.2. Persistence and degradability

HYDROGEN PEROXIDE SOLUTION

Solubility in water 100000 mg/l

Rapidly degradable

12.3. Bioaccumulative potential

HYDROGEN PEROXIDE SOLUTION

Partition coefficient: n-octanol/water -1.57

12.4. Mobility in soil

Information not available

Revision nr.2 Dated 10/9/2019 Printed on 11/6/2020 Page n. 7 / 10 Replaced revision:1 (Dated 5/7/2015)

12. Ecological information .../>>

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Other adverse effects

Information not available

13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

U.S. Federal Regulations

TSCA:

All components are listed on TSCA Inventory.

Clean Air Act Section 112(b):

No component(s) listed.

Clean Air Act Section 602 Class I Substances:

No component(s) listed.

Clean Air Act Section 602 Class II Substances:

No component(s) listed.

Clean Water Act – Priority Pollutants:

No component(s) listed.

Revision nr.2 Dated 10/9/2019 Printed on 11/6/2020 Page n. 8 / 10 Replaced revision:1 (Dated 5/7/2015)

15. Regulatory information .../>

Clean Water Act – Toxic Pollutants:

No component(s) listed.

DEA List I Chemicals (Precursor Chemicals):

No component(s) listed.

DEA List II Chemicals (Essential Chemicals):

No component(s) listed.

EPA List of Lists:

313 Category Code:

No component(s) listed.

EPCRA 302 EHS TPQ:

7722-84-1 HYDROGEN PEROXIDE SOLUTION

EPCRA 304 EHS RQ:

7722-84-1 HYDROGEN PEROXIDE SOLUTION

CERCLA RQ:

No component(s) listed.

EPCRA 313 TRI:

No component(s) listed.

RCRA Code:

No component(s) listed.

CAA 112 (r) RMP TQ:

No component(s) listed.

State Regulations

Massachussetts:

7722-84-1 HYDROGEN PEROXIDE SOLUTION

Minnesota:

7722-84-1 HYDROGEN PEROXIDE SOLUTION

New Jersey:

7722-84-1 HYDROGEN PEROXIDE SOLUTION

New York:

7722-84-1 HYDROGEN PEROXIDE SOLUTION

Pennsylvania:

7722-84-1 HYDROGEN PEROXIDE SOLUTION

California:

7722-84-1 HYDROGEN PEROXIDE SOLUTION

Proposition 65:

This product does not contain any substances know to the State of California to cause cancer, reproductive harm or birth defects.

International Regulations

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Candadian WHMIS

Information not available

Revision nr.2 Dated 10/9/2019 Printed on 11/6/2020 Page n. 9 / 10 Replaced revision:1 (Dated 5/7/2015)

16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

H271 May cause fire or explosion; strong oxidiser.

H272 May intensify fire; oxidiser.
H302 Harmful if swallowed.
H332 Harmful if inhaled.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.H335 May cause respiratory irritation.

LEGEND:

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAA 112 ® RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112®)
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: EC Regulation 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

GENERAL BIBLIOGRAPHY:

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh Registry of Toxic Effects of Chemical Substances
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy
- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Comunication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112® of the Clean Air Act
- Massachussetts 105 CMR Department of public health 670.000: "Right to Know"
- Minensota Chapter 5206 Departemnt Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.

Revision nr.2 Dated 10/9/2019 Printed on 11/6/2020 Page n. 10 / 10 Replaced revision:1 (Dated 5/7/2015)

16. Other information ... / >>

- NTP. 2011. Report on Carcinogens, 12th Edition.- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Product classification derives from criteria established by the OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200), unless determined otherwise in Section 11 and 12. The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review: The following sections were modified:

01/02/03/04/05/08/09/10/11/12/13/14/15/16.