

**Safety Data Sheet**

According to U.S.A. Federal Hazcom 2012

**1. Identification**

1.1. Product identifier

Code: **TEPOXQ-BIANCO**  
Product name: **TEPOX Q BIANCO**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **PAINT FOR DECORATION**

Identified Uses	Industrial	Professional	Consumer
<b>ADHESIVE SYSTEM/TREATMENT FOR STONE SECTOR</b>	✓	✓	-

1.3. Details of the supplier of the safety data sheet

Name: **TENAX SPA**  
Full address: **Via I Maggio, 226**  
District and Country: **37020 Volargne (VR) Italy**  
Tel: **+39 045 6887593**  
Fax: **+39 045 6862456**  
e-mail address of the competent person responsible for the Safety Data Sheet: **msds@tenax.it**  
Supplier: **Tenax Usa**  
**7606 Whitehall Executive Center Drive Suite 400, 28273 Charlotte NC, US**  
Tel. **001 7045831173** - Fax **001 7045833166**  
**info@tenaxusa.com**

1.4. Emergency telephone number

For urgent inquiries refer to: **Infotrac**  
**US and Canada: 1-800-535-5053**  
**Int'l: 1-352-323-3500**  
**info@infotrac.net**

**2. Hazards identification**

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200). The product thus requires a safety datasheet. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

<p>Classification and Hazard Statement</p> <ul style="list-style-type: none"> <li>Flammable liquid, category 3</li> <li>Reproductive toxicity, category 1B</li> <li>Eye irritation, category 2</li> <li>Skin irritation, category 2</li> <li>Specific target organ toxicity - single exposure, category 3</li> </ul>	<ul style="list-style-type: none"> <li>Flammable liquid and vapour.</li> <li>May damage fertility or the unborn child.</li> <li>Causes serious eye irritation.</li> <li>Causes skin irritation.</li> <li>May cause drowsiness or dizziness.</li> </ul>
--	--

Hazard pictograms:



Signal words: **Danger**

Hazard statements:

### 2. Hazards identification ... / >>

<b>H226</b>	Flammable liquid and vapour.
<b>H360</b>	May damage fertility or the unborn child.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H336</b>	May cause drowsiness or dizziness.

Precautionary statements:

Prevention:

<b>P210</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
<b>P261</b>	Avoid breathing dust / fume / gas / mist / vapours / spray.
<b>P202</b>	Do not handle until all safety precautions have been read and understood.
<b>P242</b>	Use only non-sparking tools.
<b>P201</b>	Obtain special instructions before use.
<b>P280</b>	Wear protective gloves/ protective clothing / eye protection / face protection.
<b>P271</b>	Use only outdoors or in a well-ventilated area.
<b>P264</b>	Wash the hands thoroughly after handling.
<b>P240</b>	Ground / bond container and receiving equipment.
<b>P243</b>	Take precautionary measures against static discharge.
<b>P241</b>	Use explosion-proof electrical / ventilating / lighting / . . . / equipment.

Response:

<b>P305+P351+P338</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
<b>P303+P361+P353</b>	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water / shower.
<b>P308+P313</b>	IF exposed or concerned: Get medical advice / attention.
<b>P312</b>	Call a POISON CENTER / doctor / . . . / if you feel unwell.
<b>P332+P313</b>	If skin irritation occurs: Get medical advice / attention.
<b>P337+P313</b>	If eye irritation persists: Get medical advice / attention.
<b>P304+P340</b>	IF INHALED: remove person to fresh air and keep comfortable for breathing.
<b>P302+P352</b>	IF ON SKIN: wash with plenty of water / . . .
<b>P362+P364</b>	Take off contaminated clothing and wash it before reuse.
<b>P370+P378</b>	In case of fire: use CO <sub>2</sub> , sand, powder to extinguish.

Storage:

<b>P403+P235</b>	Store in a well-ventilated place. Keep cool.
<b>P403+P233</b>	Store in a well-ventilated place. Keep container tightly closed.
<b>P405</b>	Store locked up.

Disposal:

<b>P501</b>	Dispose of contents / container according to applicable law.
-------------	--

#### 2.2. Other hazards

Information not available

### 3. Composition/information on ingredients

#### 3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification:
<b>1-METHOXY-2-PROPANOL</b>		
CAS 107-98-2	55 ≤ x < 57	<b>Flammable liquid, category 3 H226, Specific target organ toxicity - single exposure, category 3 H336</b>
EC 203-539-1		
INDEX 603-064-00-3		
REACH Reg. 01-2119457435-35		
<b>2-BUTOXYETHANOL</b>		
CAS 111-76-2	12.5 ≤ x < 13.5	<b>Flammable liquid, category 4 H227, Acute toxicity, category 4 H302, Acute toxicity, category 4 H332, Eye irritation, category 2 H319, Skin irritation, category 2 H315</b>
EC 203-905-0		
INDEX 603-014-00-0		
REACH Reg. 01-2119475108-36		

### 3. Composition/information on ingredients ... / >>

#### 2-methoxypropanol

CAS 1589-47-5  $0.1 \leq x < 0.4$

**Flammable liquid, category 3 H226, Reproductive toxicity, category 1B H360, Serious eye damage, category 1 H318, Skin irritation, category 2 H315, Specific target organ toxicity - single exposure, category 3 H335**

EC 216-455-5  
 INDEX 603-106-00-0

\* There is a batch to batch variation.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

### 4. First-aid measures

#### 4.1. Description of first aid measures

**EYES:** Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

**SKIN:** Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

**INGESTION:** Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

**INHALATION:** Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

#### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

### 5. Fire-fighting measures

#### 5.1. Extinguishing media

##### SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

##### UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

#### 5.2. Special hazards arising from the substance or mixture

##### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

#### 5.3. Advice for firefighters

##### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

##### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

### 6. Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

#### 6.2. Environmental precautions

### 6. Accidental release measures ... / >>

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## 7. Handling and storage

### 7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3. Specific end use(s)

Information not available

## 8. Exposure controls/personal protection

### 8.1. Control parameters

Regulatory references:

USA	NIOSH-REL	NIOSH publication No. 2005-149, 3th printing, 2007.
USA	OSHA-PEL	Occupational Exposure Limits - Limits for Air Contaminants TABLE Z-1-1910.1000.
USA	CAL/OSHA-PEL	California Division of Occupational Safety and Health (Cal-OSHA) Permissible Exposure Limits (PELs).
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2022

#### 1-METHOXY-2-PROPANOL

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH	-	184	50	368	100	
OEL	EU	375	100	568	150	SKIN
CAL/OSHA	USA	360	100	540	150	SKIN
NIOSH	USA	360	100	540	150	

#### 2-BUTOXYETHANOL

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH	-	97	20			
OEL	EU	98	20	246	50	SKIN
OSHA	USA	240	50			SKIN
CAL/OSHA	USA	97	20			SKIN
NIOSH	USA	24	5			SKIN

Legend:

### 8. Exposure controls/personal protection ... / >>

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

#### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must comply with current regulations.

##### HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (OSHA 29 CFR 1910.138): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

##### SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear. Wash body with soap and water after removing protective clothing.

##### EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

##### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose limit of use will be defined by the manufacturer (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84, OSHA 29 CFR 1910.134.

##### ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

**HAND PROTECTION:** Protect hands with work gloves for protection from chemical agents in nitrile or fluoroelastomer (EN 374-1: 2016) at least type B or higher based on the risk assessment carried out by the company. Breakthrough time > 480 minutes.

Material thickness:

##### NITRILE

short contact > 0.38 mm

prolonged contact > 0.55 mm

##### FLUOROELASTOMER

short contact > 0.50 mm

prolonged contact > 1.50 mm

### 9. Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	white	
Odour	characteristic	
Odour threshold	not available	
pH	not available	
Melting point / freezing point	not available	
Initial boiling point	> 35 °C (95 °F)	
Boiling range	not available	
Flash point	32 °C (89,6 °F)	
Evaporation rate	not available	
Flammability	not available	
Lower inflammability limit	not available	
Upper inflammability limit	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Vapour pressure	not available	
Vapour density	not available	
Relative density	1.18 g/cm <sup>3</sup>	
Solubility	not available	
Partition coefficient: n-octanol/water	not available	
Auto-ignition temperature	not available	
Decomposition temperature	not available	

### 9. Physical and chemical properties ... / >>

Viscosity	not available
Explosive properties	not available
Oxidising properties	not available
9.2. Other information	
VOC :	68,68 % - 810,42 g/litre

### 10. Stability and reactivity

#### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

##### 1-METHOXY-2-PROPANOL

Dissolves various plastic materials. Stable in normal conditions of use and storage.

##### 2-BUTOXYETHANOL

Decomposes under the effect of heat.

#### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

#### 10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

##### 1-METHOXY-2-PROPANOL

May react dangerously with: strong oxidising agents, strong acids.

##### 2-BUTOXYETHANOL

May react dangerously with: aluminium, oxidising agents. Forms peroxides with: air.

#### 10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

##### 1-METHOXY-2-PROPANOL

Avoid exposure to: air.

##### 2-BUTOXYETHANOL

Avoid exposure to: sources of heat, naked flames.

#### 10.5. Incompatible materials

##### 1-METHOXY-2-PROPANOL

Incompatible with: oxidising substances, strong acids, alkaline metals.

#### 10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

##### 2-BUTOXYETHANOL

May develop: hydrogen.

### 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

#### 11.1. Information on toxicological effects

##### Metabolism, toxicokinetics, mechanism of action and other information

Information not available

##### Information on likely routes of exposure

Information not available

##### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

##### Interactive effects

**11. Toxicological information** ... / >>

Information not available

ACUTE TOXICITY

**2-BUTOXYETHANOL**

LD50 (Oral): 1200 mg/kg Guinea pig  
LC50 (Inhalation vapours): 2.2 mg/l/4h Rat

**1-METHOXY-2-PROPANOL**

LD50 (Oral): 5300 mg/kg Rat  
LD50 (Dermal): 13000 mg/kg Rabbit  
LC50 (Inhalation vapours): 54.6 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

Carcinogenicity Assessment:

107-98-2 1-METHOXY-2-PROPANOL  
ACGIH:: A4  
111-76-2 2-BUTOXYETHANOL  
ACGIH:: A3  
IARC:3

REPRODUCTIVE TOXICITY

May damage fertility or the unborn child

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

**12. Ecological information**

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

12. Ecological information ... / >>

2-BUTOXYETHANOL

LC50 - for Fish	1474 mg/l/96h Oncorhynchus mykiss
EC50 - for Crustacea	1550 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	1840 mg/l/72h Pseudokirchneriella subcapitata
Chronic NOEC for Fish	> 100 mg/l Brachydanio rerio - NOEC 21d
Chronic NOEC for Crustacea	100 mg/l Daphnia magna - NOEC 21d

1-METHOXY-2-PROPANOL

LC50 - for Fish	> 1000 mg/l/96h Oncorhynchus mykiss
EC50 - for Crustacea	> 21000 mg/l/48h Daphnia magna

12.2. Persistence and degradability

2-BUTOXYETHANOL

Solubility in water	1000 - 10000 mg/l
Rapidly degradable	

1-METHOXY-2-PROPANOL

Solubility in water	1000 - 10000 mg/l
Rapidly degradable	

12.3. Bioaccumulative potential

2-BUTOXYETHANOL

Partition coefficient: n-octanol/water	0.81
--	------

1-METHOXY-2-PROPANOL

Partition coefficient: n-octanol/water	< 1
--	-----

BCF	< 2
-----	-----

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

12.6. Other adverse effects

Information not available

13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.  
Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.  
**CONTAMINATED PACKAGING**  
Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.



**14. Transport information**

14.1. UN number

ADR / RID, IMDG, IATA: 1263

14.2. UN proper shipping name

ADR / RID: PAINT  
IMDG: PAINT  
IATA: PAINT

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3



IMDG: Class: 3 Label: 3



IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards

ADR / RID: NO  
IMDG: NO  
IATA: NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 30 Special provision: -	Limited Quantities: 5 L	Tunnel restriction code: (D/E)
IMDG:	EMS: F-E, S-E	Limited Quantities: 5 L	
IATA:	Cargo: Passengers: Special provision:	Maximum quantity: 220 L Maximum quantity: 60 L A3, A72, A192	Packaging instructions: 366 Packaging instructions: 355

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

**15. Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

U.S. Federal Regulations

TSCA:

All components of this product are listed on US Toxic Substances Control Act (TSCA) Inventory or are exempt from the listing / notification requirements.

Clean Air Act Section 112(b):

107-98-2 1-METHOXY-2-PROPANOL (Glycol ethers)

Clean Air Act Section 602 Class I Substances:

No component(s) listed.

**15. Regulatory information** ... / >>

Clean Air Act Section 602 Class II Substances:

No component(s) listed.

Clean Water Act – Priority Pollutants:

No component(s) listed.

Clean Water Act – Toxic Pollutants:

No component(s) listed.

DEA List I Chemicals (Precursor Chemicals):

No component(s) listed.

DEA List II Chemicals (Essential Chemicals):

No component(s) listed.

EPA List of Lists:

313 Category Code:

107-98-2      1-METHOXY-2-PROPANOL (Glycol ethers)

EPCRA 302 EHS TPQ:

No component(s) listed.

EPCRA 304 EHS RQ:

No component(s) listed.

CERCLA RQ:

No component(s) listed.

EPCRA 313 TRI:

107-98-2      1-METHOXY-2-PROPANOL (Glycol ethers)

RCRA Code:

No component(s) listed.

CAA 112 (r) RMP TQ:

No component(s) listed.

State Regulations

Massachussets:

107-98-2      1-METHOXY-2-PROPANOL (Glycol ethers)  
111-76-2      2-BUTOXYETHANOL

Minnesota:

107-98-2      1-METHOXY-2-PROPANOL (Glycol ethers)  
111-76-2      2-BUTOXYETHANOL

New Jersey:

107-98-2      1-METHOXY-2-PROPANOL (Glycol ethers)  
111-76-2      2-BUTOXYETHANOL

New York:

No component(s) listed.

Pennsylvania:

107-98-2      1-METHOXY-2-PROPANOL (Glycol ethers)  
111-76-2      2-BUTOXYETHANOL

California:

107-98-2      1-METHOXY-2-PROPANOL (Glycol ethers)  
111-76-2      2-BUTOXYETHANOL

Proposition 65:

This product does not contain any substances know to the State of California to cause cancer, reproductive harm or birth defects.

International Regulations

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

### 15. Regulatory information ... / >>

Substances subject to the Rotterdam Convention:  
None

Substances subject to the Stockholm Convention:  
None

### 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>H226</b>	Flammable liquid and vapour.
<b>H227</b>	Combustible liquid.
<b>H360</b>	May damage fertility or the unborn child.
<b>H302</b>	Harmful if swallowed.
<b>H332</b>	Harmful if inhaled.
<b>H318</b>	Causes serious eye damage.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H335</b>	May cause respiratory irritation.
<b>H336</b>	May cause drowsiness or dizziness.

**LEGEND:**

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAA 112 © RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112©)
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: Regulation (EC) 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REACH: Regulation (EC) 1907/2006
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

**GENERAL BIBLIOGRAPHY:**

- GHS rev. 3
  - The Merck Index. 10th Edition
  - Handling Chemical Safety
  - Niosh - Registry of Toxic Effects of Chemical Substances
  - INRS - Fiche Toxicologique (toxicological sheet)
  - Patty - Industrial Hygiene and Toxicology
  - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
  - ECHA website
  - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy
- 6 NYCRR part 597

**16. Other information** ... / >>

- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Communication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112© of the Clean Air Act
- Massachusetts 105 CMR Department of public health 670.000: "Right to Know"
- Minensota Chapter 5206 Departemnt Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

**CALCULATION METHODS FOR CLASSIFICATION**

Product classification derives from criteria established by the OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200), unless determined otherwise in Section 11 and 12. The data for evaluation of chemical-physical properties are reported in section 9.

**Changes to previous review:**

The following sections were modified:

01 / 03 / 08 / 09 / 11 / 12 / 14 / 15 / 16.